

TRACKSHOT

Drive Recorder F2



安装朝车内摄器须知

安装准则

- 车主须获陆交局准许, 才能到授权安装中心装置器材
- 须在车内贴告示通知乘客车里装有摄录器
- 乘客电召的德士或私召车若装有摄录器, 得先通知

摄录器规格

- 能录制影像和声音
- 须预防他人破坏或篡改 (例如锁上行车锁)
- 摄录内容最多储存七天, 过后自动删除
- 影像须显示日期、时间和车牌

保护他人资料及隐私

- 只有调查员等授权者能读取摄录内容
- 授权者须仔细记录内容读取

早报图表 / 梁锡泉



PREMIUM RECORDER

MADE IN KOREA



>25,000

TAXIs/PHCs using Trackshot

UP TO 3-YEAR WARRANTY



Model	TRACKSHOT F2
CPU Model	ARM Cortex A7
Device Channel	1CH / 2CH, World's Fastest Booting (within 6 sec)
LCD	3.5" TFT LCD / 480x320 Resistive Touch Display
Camera (image sensor)	Front : 2.4 Megapixels CMOS / Rear : 1 Megapixels CMOS
Recording Resolution	Front: 2K (2048x1152) / Rear: HD (1280x720), Night Vision
View Angle	~140° (D)
Image Frame	Front/Rear: 30/20/15/10 FPS configurable
Personal Data Protection	Outward Facing (Front and Rear) with Galvanized Seal Lock; Voice Recording Deactivation Hardcoded; SD Card Seal Lock, Password Protection; Vehicle Plate OSD configurable Pre-approved by LTA
Car Battery Protection	Immediate, 11.4/23.1V, 11.6/23.4V, 11.8/23.7V, 12.0/24.0V, 12.2/24.3V
Recording Media	microSD Card 32GB ~ 256GB, Enhanced Format-Free Safe Recording Method
G-Sensor / Super Capacitor	3D Shock Sensor / Super Capacitor
GPS	Support (optional)
PC Viewer	Windows
ADAS	LDWS (GPS required)
RTC	Mercury Cell
Power Consumption	Lowest Power Consumption (Front: min 160mA; Rear: min 120mA)@12V Lowest Standby Power (Front: min 75uA)@12V
Power Input	DC 12V~24V (Free Voltage)